

### **General Information**

MB10/12.SFL **Extended Product Type:** 1SNA111034R0400 **Product ID:** 

EAN: 3472591110340

**Catalog Description:** MB10/12.SFL Screw Clamp Terminal Blocks - For 5 x 20 and 5 x 25 fuses - with blown fuse

indicator - Grey

Long Description: - Protect your circuits with 5x20 fuse terminal blocks (fuse not supplied with terminal

blocks), - Quickly identify the defective circuit thanks to the blown fuse indicator.

### **Categories**

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

#### **Ordering**

**Minimum Order Quantity:** 25 piece **Customs Tariff Number:** 85361050 Color: Grey

### **Dimensions**

**Product Net Height:** 58 mm **Product Net Depth:** 58.5 mm **Product Net Weight:** 40 g **Product Net Width:** 12 mm

### **Technical**

12 mm Spacing: **Connection Type:** Screw clamp Function: Fuse **Number of Levels:** 

**Connecting Capacity Main Circuit:** Screw Clamp / Flexible 1x 0.5 ... 10 mm<sup>2</sup>

Screw Clamp / Rigid 1x 0.5 ... 16 mm<sup>2</sup>

Rated Current (In): Main Circuit 10 A

Rated Voltage (Ur):

Degree of Protection: acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10

**Insulation Material:** Polyamide

Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715

TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

Wire Stripping Length: 13.0 mm Recommended Screw Driver: 6 mm

acc. IEC 60947-1 1.2 N·m **Tightening Torque:** 

Manufacturer 1.4 N·m

Rated Cross-Section: 10 mm<sup>2</sup>

## Technical UL/CSA

**Connecting Capacity Main Circuit** 

UL/CSA:

Flammability According to UL94:

**Maximum Operating Voltage** 

Connecting Capacity UL/CSA:

UL/CSA:

Main Circuit 600 V

Stranded 6 AWG

## **Environmental**

**RoHS Status:** Following EU Directive 2002/95/EC August 18, 2005 and amendment

Screw Clamp / Rigid 1x 18 ... 6 AWG

Operation -55 ... +110 °C **Ambient Air Temperature:** Storage -55 ... +110 °C

## **Certificates and Declarations (Document Number)**

1SNC160001C0207-CH-A screw clamp Instructions and Manuals:

**CSA Certificate:** 1SND161039A0201 cUL Certificate: 1SND161000A0203

Data Sheet, Technical Information: 1SNC160001C0207-CH-A screw clamp

**Declaration of Conformity - CE:** 1SND225016U1000 **EAC Certificate:** 1SND161009A1100 **RoHS Information:** 1SND230023F0208

# Classifications

ETIM 4:	EC000899 - Fuse terminal block
ETIM 5:	EC000899 - Fuse terminal block
ETIM 6:	EC000899 - Fuse terminal block
Object Classification Code:	X

# **Container Information**

Package Level 1 Width:	126 mm
Package Level 1 Length:	155 mm
Package Level 1 Height:	64 mm
Package Level 1 Gross Weight:	1 kg
Package Level 1 EAN:	3472591110340
Package Level 2 Units:	250 piece
Package Level 3 Units:	12000 piece
Product Packing Type:	Box
Package Level 1 Units:	25 piece

