

## Agastat

TE Internal #: 3-1423164-1 Time Delay Relays, Knob, 125VDC Input Voltage, Timing Range (Off-Time) .2 – 2 seconds, 10A Contact Current Rating, Off-Delay, Chassis

View on TE.com >

Relays & Contactors > Relays > Time Delay Relays



Type of Control: Knob Input Voltage: 125 VDC Timing Range (Off-Time): .2 – 2 seconds Contact Current Rating: 10 A Mode of Operation: Off-Delay

## Features

## **Configuration Features**

Relay Options

Contact Arrangement

connectivity

Multiple Timing Ranges

2 Form C, DPDT, 2 C/O

#### **Electrical Characteristics**

Input Voltage	125 VDC
Contact Current Rating	10 A
Termination Features	
Relay Connection Type	Terminals
Terminal Configuration	Screw Terminals
Mechanical Attachment	
Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Chassis
Dimensions	
Product Width	82.55 mm[3.25 in]
Product Length	114.8 mm[4.52 in]
Product Height	78.4 mm[3.09 in]
Usage Conditions	
Operating Temperature Range	-30 – 75 °C

## 7022PJ

Time Delay Relays, Knob, 125VDC Input Voltage, Timing Range (Off-Time) .2 – 2 seconds, 10A Contact Current Rating, Off-Delay, Chassis



### **Operation/Application**

Repeatability (Max)	±10%
Actuating System	DC
Type of Control	Knob
Timing Range (Off-Time)	.2 – 2 seconds
Mode of Operation	Off-Delay

## **Product Compliance**

#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per

#### Solder Process Capability

#### Free

#### Not applicable for solder process capability

homogenous material. Also BFR/CFR/PVC

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## **Compatible Parts**

## 7022PJ

Time Delay Relays, Knob, 125VDC Input Voltage, Timing Range (Off-Time) .2 – 2 seconds, 10A Contact Current Rating, Off-Delay, Chassis





# Customers Also Bought



## Documents

Datasheets & Catalog Pages 5-1773450-5\_sec12\_7000

English