
EXP-0911/04/S Datasheet



Product Name // Flex Cable Connector EXP-0911 Series 4 Contact Socket 13mm-15mm Cable (Yellow Gland)

View Product Page





// Product Description:

- Plex Cable Connectors for hazardous areas
- Water and dustproof to IP68 when mated with compatible connector
- O Positive fast-acting locking ring can be turned with a gloved
- O Plug or Socket
- Q 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- O Screw Terminals

- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- O EXP-09 part codes 7mm-15mm diameter
- EXP-A9 part codes (large cable version with strain relief clamp)
 14mm-22mm diameter
- Packs of Cable Glands for differing cable diameters available separately (EXP-0980, EXP-A980)
- EXP-0990 heavy duty Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with EXP-09 or EXP-A9 Series Flex and Panel Mounting Connectors, as appropriate

// General Information:

Product Display Title:

Product Family:

Product Series: Approvals:

Body Material:

Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Man Cable Entry Size

Max Contact Accomodation Awg: Min Contact Accomodation Awg:

Max Contact Accomodation Mm2: Min Contact Accomodation Mm2:

Max Operating Temperature:

Min Operating Temperature:

Number Of Contacts: Voltage Max: Flex Cable Connectors for hazardous areas

Circular Power Connectors

EXPlora ...

UL

Polyester (PET)

Plastic Body

Socket Contact Screw

18A

58mm

UL94V-0

Flex Cable Connector

IP68 15mm

13mm

14AWG

10AWG

4mm2 2.5mm2

+55°C

-20°C 4 Contacts

600V

// Product PDF Links



EXPlora Series power connectors...