


Triad Magnetics

460 Harley Knox Blvd

Perris CA 92571

Tel: 951.277.0757 • **Fax:** 951.277.2757

Email: info@triadmagnetics.com • **Website:**
www.triadmagnetics.com

Item # N-68X, Isolation Power Transformers

Triad isolation transformers are power transformers for isolating equipment from direct connection to the power line. They are offered in a variety of voltages and case types. Triad isolation transformers are also offered in hospital type (designed with an MD suffix) which are designed and constructed to meet the low leakage current requirements for today's medical equipment. The transformers are constructed with nonconcentrically wound coils. The primary and secondary are wound on separate

[+ more](#)

[Specifications](#) | [Technical Notes](#) | [Note](#)

Specifications

Output Wattage (VA) Rating	50 W
Primary Voltage	115 V 230 V
Primary Frequency	50 Hz 60 Hz
Secondary Voltage (±5%)	115 V
Secondary Current	0.435 A
Case Type	X

Connections	Leads
Height (H)	2 9/32 in
Width (W)	3 11/16 in
Depth (D)	2 1/8 in
Mounting Width	3 1/8 in
Mounting Hole Size	3/16 in
Weight	1.70 lb

Technical Notes

Technical Notes

1. Line cord, plug and receptacle are U.L. listed and verified to meet federal specifications.
2. Connections are by leads, plugs and sockets.
3. Hi-pot tested at 1,500 VRMS.

Note

Note

Split winding