# PPCEGG3K02CLL Datasheet



## Product Name // 2 Contacts Fixed Socket 3Y Series Push Pull Connector

View Product Page

### 

#### // Product Description:

- O 2 Contacts Fixed Socket 3Y Series Push Pull Connector
- O M24x1.0mm Thread
- O Nut Installation torque 12Nm
- O Available in Straight Plug version
- O ROHS compliance
- O IP66 rated

- O Temp:-50 C to +200 C
- O Solder Terminals
- O Durability >4500 cycles
- Operating humidity up to 95%
- O Salt Spray Corrosion Test >144h
- O High packing density for space savings on panel mounts


#### // General Information:

**Product Display Title: Product Family: Product Series:** Contact Pin Material: **Coupling Nut Retention Force:** Current Max: Diameter Over Coupling Ring Mm: Durability: Fixing Nut Material: Function: Insulator: Ip Rating: Max Contact Accomodation Awg: Max Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Max Panel Thickness: Number Of Contacts: **Operating Humidity:** Panel Cut Out: Pin Pin Terminal Voltage: Pin Shell Terminal Voltage: **Push Pull Connector Series: Rohs Compliant:** Salt Spray Corrosion Test: Shielding Efficiency Min: Shielding Efficiency Max: Shock Resistance: Terminal Diameter: Thread Size: Vibration Resistance Min: Vibration Resistance Max:

3Y Series Fixed Socket Push Pull Connector **Circular Automation Connectors** Push Pull Connectors Y Series Phosphor bronze gold plated 3u" 12Nm 35A 31mm >4500 cycles Nickel Plated brass Fixed Socket Push Pull Connector PPS IP66 12AWG 4.0mm2 +200°C -50°C 10mm 2 Contacts 0.95 24.20mmx22.60mm 2100V 1550V **3Y Series** Yes 48h 95dB 80dB 100g 3mm M24x1.0mm 10Hz 2000Hz







Bulgin Datasheets 1