

Product Name // M12 Series A Code PVC In-Line

Overmould Flex Cable Connector 12 Contact Pins Pre-Wired

With 1M PVC Jacket Cable

 [View Product Page](#)



// Product Description:	
M12 Series In-Line Overmould Flex Body Connectors	Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
Water and dustproof to IP67 when mated with compatible connector	Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
Pin only	Mate with M12 Series Flex Body and Panel Mount Connectors
3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)	

// General Information:	
Product Display Title:	M12 Series In-Line Overmould Flex Body Connectors
Product Family:	Circular Automation Connectors
Product Series:	M12 Series
Body Material:	PVC
Cable Length:	1m
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	1.5A
Diameter Over Coupling Ring Mm:	20mm
Function:	Inline Connector Single Ended Cable
Ip Rating:	IP67
Max Operating Temperature:	+80°C
Min Operating Temperature:	-25°C
Number Of Contacts:	12 Contacts
Pin Layout Code:	A Code
Sheath Material:	PVC
Thread Size:	M12 x 1
Voltage Max:	30V

// Product PDF Links



M12 Series automation connectors...