


PXPTPU12FBF08ACL010PUR Datasheet

**Product Name // M12 Series A Code TPU Overmould Flex
Body Cable Connector 8 Contact Socket Pre-Wired With 1M
PUR Jacket Cable**

 [View Product Page](#)



// Product Description:

- ⬢ M12 Series Overmould Flex Body Connectors
 - ⬢ Water and dustproof to IP67 when mated with compatible connector
 - ⬢ Socket only
 - ⬢ 3, 4, 5, 8, 12 Contact (3, 8, 12 Contact are A Code, 4 Contact are choice of A Code or D Code, 5 Contact are choice of A Code or B Code)
- ⬢ Overmould cable Termination with choice of lead lengths and choice of PVC or PUR jacket cable, depending on part code
 - ⬢ Choice of Sealing Caps available separately to maintain IP rating of unmated connectors
 - ⬢ Mate with M12 Series Inline Body and Panel Mount Connectors

// General Information:

Product Display Title:	M12 Series Overmould Flex Body Connectors
Product Family:	Circular Automation Connectors
Product Series:	M12 Series
Body Material:	TPU
Cable Length:	1m
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	2A
Diameter Over Coupling Ring Mm:	20mm
Function:	Flex Connector Single Ended Cable
Ip Rating:	IP67
Max Operating Temperature:	+80°C
Min Operating Temperature:	-25°C
Number Of Contacts:	8 Contacts
Pin Layout Code:	A Code
Rohs Compliant:	Yes
Sheath Material:	PUR
Thread Size:	M12 x 1
Voltage Max:	30V

// Product PDF Links

 [M12 Series automation connectors...](#)