S8 Relay Series *Miniature high voltage relay*



58-12:04 52:14

The S8 series is a miniature high voltage reed relay for applications where space saving is a prime consideration.


The coil pins are positioned near the centre of the relay while the contact pins are near the ends to give improved isolation between the High Voltage contacts and the low voltage coil.

- Space saving package
- Isolation Voltage across contacts 4kV or 5kV (dependant on coil voltage)
- Isolation Voltage 7kV contact to coil
- 2.5A carry current

Contact Specification	1		5V coil	12V coil	24V coil
Switch action				SPST (Form /	(4
Material				Rhodium	
Isolation across conta		kV DC or AC peak	4	4	5
Switching Power Max.		VA		100	
Switching Voltage Max		V		350dc/300ac	
Switching Current Max	(.	A DC or AC peak		1.0	
Carry Current Max	А	DC		2.5	
Capacitance across	рF	coil to screen		<0.1	
contacts		grounded			
Lifetime operatio	ns	dry switching		10 ⁹	
		100W switching		107	
Contact Resistance		max (typical)		80 (30)	
Insulation Resistance	Ωm	in (typical)		10^{10} (10^{13})	
Coil Specification					
Must Operate Voltage		DC	4	9.6	19
Must Release Voltage		DC	1	2	3
Operate Time		diode fitted	1	1	1
Release Time		diode fitted	0.5	0.5	0.5
Resistance	Ω		120	750	1550
Relay Specification					
Isolation contact/coil				7	
Insulation resistance					
to all terminals	Ωm	in (typical)		TBC	
Envirnonmental			40.1 05		
Operating Temp range			-40 to +85		
Storage Temp range	°C	Malla Mala and a la da la	-40 to +125		
Standard Parts		Volts Vdc Isolation acros			
S8-0504	5		4		
S8-1204	12		4		
S8-2405	24		5		

Custom versions can be made for particular applications. Please contact Cynergy3 with your requirements.

Mechanical Dimensions



Cynergy3 Components Ltd. 7 Cobham Road Ferndown Industrial Estate Wimborne, Dorset BH21 7PE *Telephone +44 (0) 1202 897969*

Email:sales@cynergy3.com

ISO9001 CERTIFIED

www.cynergy3.com

© 2013 Cynergy3 Components, All Rights Reserved. Specifications are subject to change without prior notice. Cynergy3 Components and the Cynergy3 Components logo are trademarks of Cynergy3 Components Limited.

Encapsulant: Epoxy

Pins 0.635mm Square ±0.05mm. Pins 1 & 2 Tin over Nickel plated, on CuSn6 Phospher Bronze. Pins 3 & 4 Tin plated on NiFe Nickel Iron. Case Material Nylon.