



NOTES:

1. INTERFACE PER MIL-STD-348, FIG. 301-1.
2. MATERIALS:
 - INSULATOR: TEFLON, ASTM D1710
 - GASKET: SILICONE RUBBER, A-A-59588
 - SPRING WASHER: BER. COPPER, ASTM B196
 - ALL OTHER METAL PARTS: BRASS, ASTM B16
3. FINISHES:

CENTER CONTACT SPRING WASHER SLEEVE BUSHING	}	.000200 MIN SILVER PLATE PER ASTM B700 OVER .000020 MIN NICKEL PER AMS-QQ-N-290 (RoHS)
--	---	---

ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER
.000050 MIN COPPER PER ASTM B734 (RoHS)
4. ELECTRICAL CHARACTERISTICS:
 - 50 OHMS, 0.5 WATT ±1%, NON-INDUCTIVE
5. SWR LESS THAN 1.08 OR RETURN LOSS -27.96 dB @ 100 MHz.
6. WEIGHT: 22.6 GRAMS

KA-89-15

REVISIONS

ISSUE	CHANGES
7	CN 38173 E REDRAWN DCT 1/8/01
8	CN 38366 E TML 08/07/01
K	REVISED PER DMF304 & ER041875 KPL 5/15/12

CUSTOMER
SALES
DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1	
APPROX SURFACE AREA	
CAGE CODE: 91836	
REF:	
TERMINATION, TNC 50 OHM, 1%, 1/2 W	
DRAWN A.T.	DATE 11/22/67
DESIGN	DATE
APPR. MS	DATE 6/25/69
<div style="display: inline-block; vertical-align: middle; font-size: 0.8em; margin-left: 5px;"> Winchester Electronics Corporation 62 Barnes Industrial Road North Wallingford, Connecticut 06492 </div>	

KA-89-15