

7012SFX Product Details



7012SFX

(5 - 1423159 - 4)

TE Internal Number: 5 - 1423159 - 4

 [Active](#)
 [Add to Part List](#)

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- ? 7000 Electropneumatic Timing Series
- ? Time Delay Relay
- ? Input Voltage = 250 VDC
- ? Contact Arrangement = 2 Form C, DPDT, 2 C/O
- ? Contact Rating = 10A @ 240 VAC

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)
- [Request Samples](#)



Documentation & Additional Information

Product Drawings:

- ? None Available

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Time Delay Relay
- ? Termination Type = Screw Terminal

Electrical Characteristics:

- ? Input Voltage (VDC) = 250
- ? Contact Rating = 10A @ 240 VAC

Body Related Features:

- ? [Series](#) = 7000 Electropneumatic Timing

Contact Related Features:

- ? Mounting Options = Panel Mount
- ? Mode of Operation = On -Delay
- ? Delay Time = 1 minute to 10 minutes
- ? Type of Control = Knob
- ? Repeatability, Max. = $\pm 10\%$
- ? Approved Standards = CE Approved, CSA Certified, FM Approved, UL Listed
- ? Option = Hardware and Adjustment for Horizontal Operation
- ? Approx. Dimensions (L x W x H) (mm [in]) = 114.80 x 65.30 x 71.90 [4.523 x 2.572 x 2.832]

Configuration Related Features:

- ? [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- ? Multiple Timing Ranges = Without

Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Not relevant for lead free process

Conditions for Usage:

- ? Temperature Range (°C) = -30 - +75

Other:

- ? Brand = Agastat