

# CABLE ASSEMBLIES

## BNC MALE / MALE



<u>RG58C/U</u>	<u>RG59B/U</u>	<u>RG174/U</u>	<u>RG62A/U</u>	<u>LENGTH</u>
795-2500	795-2510	795-2516	795-2521	12 inches
795-2501	795-2511	795-2517	795-2522	24 inches
795-2502	795-2512	795-2518	795-2523	36 inches
795-2503	795-2513	795-2519	795-2524	48 inches
795-2504	795-2514	795-2520	795-2525	60 inches
795-2505	795-2515			72 inches
795-2506				120 inches
795-2507				180 inches

**1ST END-** Crimp BNC male  
Plated brass body  
Gold plated brass  
center contact.  
Black PVC boot.

**CABLE**  
RG58C/U (50 OHM)  
RG59B/U (75 OHM)  
RG174/U (50 OHM)  
RG62A/U (93 OHM)

**2ND END-**  
Same as 1st end.

## RIGHT ANGLE BNC MALE / MALE



<u>RG58C/U</u>	<u>LENGTH</u>
795-2530	18 inches
795-2531	24 inches
795-2532	36 inches
795-2533	48 inches
795-2534	60 inches

**1ST END-** Crimp BNC male right angle.  
Plated brass body.  
Gold plated brass center contact.  
Black PVC boot.

**CABLE-** RG58C/U

**2ND END-** Same as 1st end.

## BNC FEMALE / MALE



<u>RG58C/U</u>	<u>RG59B/U</u>	<u>LENGTH</u>	<b>1ST END-</b>
795-2536	795-2556	12 inches	Crimp BNC female. Plated brass body.
795-2537		24 inches	Gold plated beryllium copper center contact.
795-2538		36 inches	Black insulated flexible boot.
795-2539		48 inches	
795-2540		60 inches	

**CABLE-** RG58C/U or RG59B/U

**2ND END-** Crimp BNC male.  
Plated brass body  
Gold plated center contact  
Black insulated flexible boot.

## UHF MALE / BNC MALE



<u>RG58C/U</u>	<u>LENGTH</u>
795-2546	18 inches
795-2547	24 inches
795-2548	36 inches
795-2549	48 inches
795-2550	60 inches

**1ST END-** Crimp UHF male.  
Plated brass body.  
Plated brass center contact.  
Black insulated flexible boot.

**CABLE-** RG58C/U

**2ND END-** Crimp BNC male.  
Plated brass body  
Gold plated brass center contact  
Black insulated flexible boot.

## BNC FEMALE / FEMALE



<u>RG58C/U</u>	<u>LENGTH</u>	<b>1ST END-</b>
795-2541	12 inches	Crimp BNC female. Plated brass body.
795-2542	24 inches	Gold plated beryllium copper center contact.
795-2543	36 inches	Black insulated flexible boot.
795-2544	48 inches	
795-2545	60 inches	

**CABLE-** RG58C/U

**2ND END-** Same as 1st end.

## UHF MALE / MALE



<u>RG58C/U</u>	<u>LENGTH</u>	<b>1ST END-</b>
795-2551	18 inches	Crimp UHF male. Plated brass body.
795-2552	24 inches	Plated brass center contact. Black insulated flexible boot.
795-2553	36 inches	Non-constant impedance
795-2554	48 inches	
795-2555	60 inches	

**CABLE-** RG58C/U

**2ND END-** Same as 1st end.

## BNC MALE ONE END



<u>RG58C/U</u>	<u>LENGTH</u>	<b>1ST END-</b>
795-2634	60 inches	Crimp BNC male. Plated brass body. Gold plated brass center contact. Black insulated flexible boot.

**CABLE-** RG58C/U, black

## DOUBLE BANANA PLUG / BNC MALE



<u>RG58C/U</u>	<u>LENGTH</u>	<b>1ST END-</b>
795-2600	18 inches	Double banana plug. Nickel plated brass body.
795-2601	24 inches	Nickel plated beryllium copper spring. Black polypropylene insulation.
795-2602	36 inches	
795-2603	48 inches	
795-2604	60 inches	

**CABLE-** RG58C/U

**2ND END-** Crimp BNC male  
Plated brass body.  
Gold plated brass center contact.  
Black insulated flexible boot.

