



Circuit Board Indicators

Panel Mount Indicators

Solid State Lighting

Traffic Signals

Vehicle Lighting

Rail

Obstruction Lighting

Hazardous Area Lighting

Heliport Lighting

how to purchase

[sales contacts](#)

[stock check](#)

search

Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

[find](#)

Part # / Text Search

Part No.:

Text Search:

[search](#)

quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)


**Application Notes
FAQs**

**Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives**

Circuit Board Indicators - Through Hole Indicators

P/N# 5682211023F	3 mm Lens
Description	3 mm Quad-Level CBI R-X-G-Y
Package Options	5 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	with Quad Level Housing
Configuration	3 mm Lens
Viewing	Right Angle
Viewing Angle	45
Test Current (mA)	10mA

Absolute Maximum Ratings (Ta = 25 °)



Distributor Stock Check

Check stock with our distributors now.

5682211023F

[check stock](#)

Operating Characteristics

LED Position	Found in position(s): 1	Found in position(s): 2	Found in position(s): 3	Found in position(s): 4
Color	Red	Blank	Green	Yellow
Lamp Type	Single Color	Single Color	Single Color	Single Color
LED Type	High Efficiency		High Efficiency	High Efficiency
Intensity Min (mcd)	8.7		32.0	10.0
Intensity Typ (mcd)	29.0		50.0	
Intensity Max (mcd)				50
Fwd Voltage Min				
Fwd Voltage Typ				
Fwd Voltage Max				
Dom Wavelength Min (nm)				
Dom Wavelength Typ (nm)				
Dom Wavelength Max (nm)				
Power Dissipation Max (mW)	100		100	60
Backlighting				
Pitch Between Vertical				
Pitch Between Horizontal				
Lum Intensity Min				
Lum Intensity Typ				
Lum Intensity Max				