



- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N#	1210 Package Tri - Color
5977711302F	
Description	

Region:
Product Line:
Circuit Board Indicators

Solder Temp	260Â° for 10 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C

Distributor Stock Check

Check stock with our distributors now.

5977711302F



Operating Characteristics

LED Position	
Color	Blue / Green / Red
Lamp Type	Tri-Color / Tri - Color / Tri -Color
LED Type	AllnGaP / InGaN / InGaN
Intensity Min (mcd)	25.0 / 99.0 / 40.0
Intensity Typ (mcd)	40.0 / 160.0 / 80.0
Intensity Max (mcd)	60 / 180 /
Fwd Voltage Min	3.4 / 3.4 /
Fwd Voltage Typ	1.4
Fwd Voltage Max	4.0 / 4.0 /
Dom Wavelength Min (nm)	2.4
Dom Wavelength Typ (nm)	470 / 525 / 626
Dom Wavelength Max (nm)	72 / 120 / 120
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Check stock with our distributors now.

5977711302F

Please note that the stock check **is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Please select a Product Line to search.

Circuit Board Indicators

Part No.:

Text Search:

[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)