



Note 1. area indicates for 18 pos. Connector during soldering assembly process. Design to breakaway after assembly.

Note 2. These products are one-piece units with molded-in contacts and rubber packing, marking these connectors waterproof (IPX5 or equivalent).

LTR.	DATE	BY	REV. DESCRIPT
⑨	NOV. 04 2008	S. ARAI	ADDED DIM. CHANGED FINISH
⑧	NOV. 01 2005	K. ONO	DELETED DIMENSION (0.45)
⑦	JUN. 11 2004	K. OAKU	ADD NOTE 2
⑥	MAR. 18 2003	T. ODA	ADD CONTACT NUMBER

⑤	NOV. 28 2001	K. ONO	CHANGED SHAPE	5	SCREW	Brass	2	Nickel plating	M2
④	OCT. 25 2001	K. ONO	CHANGED SHAPE <td>4</td> <td>LATCH</td> <td>Phosphor bronze</td> <td>2</td> <td>Nickel plating</td> <td></td>	4	LATCH	Phosphor bronze	2	Nickel plating	
③	OCT. 11 2001	K. ONO	CHANGED SHAPE <td>3</td> <td>POWER SUPPLY CONTACT</td> <td>Phosphor bronze</td> <td>2</td> <td>Gold plating</td> <td></td>	3	POWER SUPPLY CONTACT	Phosphor bronze	2	Gold plating	
②	JUL. 12 2001	K. ONO	CHANGED SHAPE <td>2</td> <td>SIGNAL CONTACT</td> <td>Phosphor bronze</td> <td>16</td> <td>Gold plating</td> <td></td>	2	SIGNAL CONTACT	Phosphor bronze	16	Gold plating	
①	JUN. 29 2001	K. ONO	CHANGED SHAPE <td>1</td> <td>INSULATOR</td> <td>LCP resin</td> <td>1</td> <td></td> <td>UL94V-0 Black</td>	1	INSULATOR	LCP resin	1		UL94V-0 Black

LTR.	DATE	BY	REV. DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
------	------	----	---------------	-----	-----------	----------	-----	--------	------

DATE	SCALE	UNIT	3RD. A. P	HONDA TSUSHIN KOGYO CO., LTD.					
MAY. 30 (2001)	4/1	mm (INCH)		DR.	DE.	CHK.	CHK.	APP.	NAME
APP. DATE & REV.				S. ARAI	K. ONO	K. ONO		H. EBIHARA	Male Connector Right Angle SMT Type
				PART NO. BCL-C18LMYG					REV. 9H