



RECOMMENDED
PANEL CUT-OUT DIMENSIONS
(t=1.12±0.08)

CONTACT DETAIL
(SCALE=5/1)

RECOMMENDED P.C.B. LAYOUT
(MOUNT SIDE VIEW) (t=1.6)
(SCALE=4/1)

NOTE1. CONTACT PLATING
CONTACT AREA: Pd/Ni 0.5µm + GOLD 0.1µm MIN.
TERMINAL AREA: GOLD 0.05µm
ALL OVER NICKEL UNDERPLATED

6	HOLD DOWN	PHOSPHOR BRONZE	2	NICKEL	
5	SQR. NUT	BRASS	2	NICKEL	M2x0.4
4	SHELL	STEEL	1	NICKEL	
3	CONTACT	PHOSPHOR BRONZE	68	SEE NOTE 1	
2	INSULATOR B	LCP	1		UL94V-0 BLACK
1	INSULATOR A	PPS	1		UL94V-0 BLACK

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE	
	Apr. 15, 2013		2 / 1			3RD. A. P					
APP. DATE&REV.							HTK HONDA TSUSHIN KOGYO CO., LTD.				
DR.	DE.	CHK.	CHK.	APP.	NAME		0.8mm SPACING 68POS. FEMALE CONNECTOR SMT TYPE				
A. TASHIRO	A. TASHIRO	M. KASAHARA	—	Y. KATO	PART NO.		HDRA-E68FYT+				
										REV.	