



WIRE AND CABLE

## MULTICORE CABLE



✓ Active

↓ **PRODUCT DRAWING**  
English

TE CONNECTIVITY (TE)

### 55A1111-20-9-9-5CF/1

Raychem

55A1111-20-9-9-5CF/1

TE Internal Number: CY6264-000

Always EU RoHS/ELV Compliant

Cable Type **Spec 55**

Overall Outside Diameter **2.13 mm [ .084 in ]**

Voltage Rating (V) **600**

Shield Material **Tin-Plated Copper**

Jacket Color **Green**

### Product Drawings

CABLE, ELECTRIC, RADIATION-CROSSLINKED, EXTRUDED, MODIFIED, FLUOROPOLYMER-INSULATED, ONE CONDUCTOR, SHIELDED, JACKETED, LIGHTWEIGHT

PDF (TIFF AVAILABLE)  
English

CABLE, ELECTRIC, RADIATION-CROSSLINKED, EXTRUDED, MODIFIED, FLUOROPOLYMER-INSULATED, ONE CONDUCTOR, SHIELDED, JACKETED, LIGHTWEIGHT

PDF (TIFF AVAILABLE)  
English

### Product Specifications



Product Specification



Wire And Cable, Electric, Radiation-Crosslinked, Extruded, Modified, Fluoropolymer-Insulated Copper Or Copper Alloy

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Cable Type	<b>Spec 55</b>
	Cable Style	<b>Round Braided Shielded &amp; Jacketed</b>
	Product Type	<b>Cable</b>
	Product Classification	<b>High Performance - Spec 44, 55 &amp; RCW</b>
Configuration Features	Number of Conductors	<b>1</b>
Electrical Characteristics	Voltage Rating (V)	<b>600</b>

Body Features	Shield Material	<b>Tin-Plated Copper</b>
	Jacket Color	<b>Green</b>
	Wire Color	<b>White</b>
	Conductor Material	<b>Tin-Coated Copper</b>
	Shield Size (AWG)	<b>38</b>

---

Dimensions	Overall Outside Diameter	<b>2.13 mm [ .084 in ]</b>
	Wire Size (AWG)	<b>20</b>
	Wire Diameter	<b>1.27 mm [ .05 in ]</b>

---

Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 150</b>
------------------	----------------------------------	------------------

---

Other	Wire Source	<b>United States</b>
-------	-------------	----------------------

---

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)